

Sand Filter, Minder - Australia



MS Series filters are one of the best sellers in the European market. With fiberglass throughout the body, inside and out, means they are reliable and suitable for all-weather performance. Tank body is available in regular pattern or cross pattern finish.

Features and benefits:

- Full Fiberglass tank, inside and out.
- UV resistance body
- Stainless steel pressure gauge
- Metal components are made by 316 grade stainless steel
- PVC black cover and PC transparent top cover for options
- With PC transparent cover, it allows easy inspection of the sand bed
- Top mounted diffuser ensure even distribution of water
- Air relief bolt enables easy release of trapped air during operation.

LX SWIMMING POOL PUMP

STP150, STP200, STP250, STP300



LX Swimming pool pump STP150 STP200 STP250 STP300

LX Pool Pump:

LX Swimming pool pump (STP150/STP200/STP250/STP300)

Features:

LX Swimming Pool Pump: STP series pool pump is most maturely swimming pool pump and is approved by customer. The pump casing applied efficient structure design with max flow, max head and low noise. Cap and filter is easy to install and unload. Liquids part is made of high reinforce engineering plastic. Applied mechanical seal type ensure watertight in long-time continuous operation. The high reinforce engineering plastic base is vibration-resistance and corrosive-resistance. STP series is preferred product for sand filter and swimming pool. Motor: Air cooling motor is suitable for Europe. The material of frame is aluminum; it is under low-noise and less-vibration and durability. Insulation class F, protection IPX5, continuous duty; Single-phase with thermal protector from T1 to ensure safety and convenience.

Certificate:

1. CCC Safety certificate
2. CE certificate in EU.
3. TUV certificate in Germany
4. SAA
5. RoHS approval

Self-priming: non-self priming performance

Applications:

- Pressure boosting of medium or large SPA pool and cleaning system of jetted bath tubs, spa pools.
- Water circulation in fishery.
- Decorative pool, water display, water processing.
- Weak corrosive liquid (weak acid and weak alkali without solid granules. Liquid temperature: +5-60°C.

Selection Notice:

- Size of pools/request current/pressure etc.
- Applied region's voltage and frequency (220-240V/60HZ, 220-240V/50HZ, 110-120V/60HZ is available.)
- Applied region's request for safety certificate.
- The fitting size.
- Type of plug. (No plug, Europe plug, UL plug is available)

LX swimming pool pump (STP35/STP50/STP75/STP100/STP120/STP150/STP200/STP250/STP300)

Item No.	Power KW/ HP	Max Head m	Max Flow L/min	Fitting Size mm	Packing Size mm	Filter Basket L	G.W(kg)	Qty/20"
STP35	0.25 / 0.35	8	160	48.5/50	470*180*295	1	6.8	1150
STP50	0.37 / 0.50	10	210	48.5/50	470*180*295	1	7.2	1150
STP75	0.55 / 0.75	10.5	240	48.5/50	495*180*295	1	8.9	1088
STP100	0.75 / 1.00	11	275	48.5/50	495*180*295	1	9.5	1088
STP120	0.90 / 1.20	13	300	48.5/50	495*180*295	1	10.5	1088
STP150	1.1/1.50	16.5	430	48.5/50/ 60.3/63	600*280*345	2.5	14	517
STP200	1.50 / 2.00	18	520	48.5/50/ 60.3/63	600*280*345	2.5	15.5	517
STP250	1.85 / 2.5	19	600	48.5/50/ 60.3/63	600*280*345	2.5	16.7	517
STP300	2.2/3.0	19	635	48.5/50/ 60.3/63	620*280*345			

POOL FITTING WATER RETURN SP-1424

Hayward USA / Emoux

1. Manufactured in white ABS, the inlets adapt to any kind of pool.
2. The return inlets return filtered, treated water to the pool. They include the “Multiflow” system, which allows the diameter, and therefore the flow rate of the water through the inlets, to be selected.
3. The suction inlets are used to connect the pool cleaner.
4. The bottom inlets are placed in the floor of the pool, returning water at floor level. They prevent dirt from settling by carrying it towards the surface.
5. Manufactured in white ABS, the inlets adapt to any kind of pool.
6. The return inlets return filtered, treated water to the pool. They include the “Multiflow” system, which allows the diameter, and therefore the flow rate of the water through the inlets, to be selected.
7. The suction inlets are used to connect the pool cleaner.
8. The bottom inlets are placed in the floor of the pool, returning water at floor level. They prevent dirt from settling by carrying it towards the surface.



Main Drain

Why do you choose us?

- All our products are manufactured with advanced equipment and strict QC procedures in order to ensure high quality.
- Guaranteeing stable and timely supply, credible quality and sincere service, our products sell well in both domestic and overseas markets.

If you are interested in any of our products, or hope to place a customized order, please contact us. We will do our best to meet your needs. we enjoy convenient access to major transportation networks